



CONCEPTUAL DRAWING  
per Quote # \_\_\_\_\_

**DIMENSIONS**

Proper installation and satisfactory operation of a standard WILDECK lift requires seven dimensions. The required dimensions are listed in the following chart.

A	Vertical Rise	_____
B	Carriage Length	_____
C	Carriage Width	_____
D	Carriage Thickness	_____
E	Load Height	_____
F	Upper Level Opening (length)	_____
G	Upper Level Opening (width)	_____

**NOTES**

1. Carriage thickness is 2" on units up to 2000# capacity . . . if carriage is no more than 6'-0" in length or width. All other carriages are 4 1/4" thick.
2. If ramp is not used, a pit can be provided. For 2" thick carriage, a 3" pit is required. For a 4 1/4" carriage, a 5" pit is needed.

WILDECK, INC. RESERVES PROPRIETARY RIGHTS TO THIS DRAWING AND DATA SHOWN THEREON. SAID DRAWING AND/OR DATA ARE CONFIDENTIAL AND ARE NOT TO BE USED OR REPRODUCED FOR ANY PURPOSE WITHOUT THE WRITTEN CONSENT OF WILDECK, INC.

THIS DRAWING IS CONCEPTUAL ONLY  
Not to be Used for Installation or Construction.

NO.	DATE	DESCRIPTION	BY
WILDECK, INC. 405 COMMERCE ST. WAUKESHA, WI 53186 (800) 325-6939 (262) 549-4000 WILDECK.COM		<b>WILDECK</b> <sup>®</sup>	
VERTICAL RECIPROCATING CONVEYOR MECHANICAL STRADDLE			
MODEL NUMBER: MLS-X		DWG No.	REV
DIMENSIONAL INFORMATION		<b>MECH STRD 3L INFO</b>	<b>0</b>