



## FEATURES & BENEFITS:

- > MEETS ANSI/ASME B20.1 SAFETY STANDARDS
- > RIGID STEEL CONSTRUCTION
- > GATE PANEL IS COUNTERWEIGHTED AND CONSTRUCTED OF FLATTENED EXP. METAL IN A TUBE & ANGLE FRAMING WITH HEAVY DUTY ROLLER CHAIN & SPROCKETS
- > GATE PANEL IS LATCHED USING AN ELECTRO-MECHANICAL INTERLOCK
- > NO LIFTING CABLES TO BREAK OR SOLENOIDS TO FAIL
- > SHIPS DISASSEMBLED WITH ANCHORS AND ASSEMBLY HARDWARE PROVIDED (WIRING BY OTHERS)
- > BEST USED WHERE ISLE SPACE IS MINIMAL WITH NO HEIGHT RESTRICTIONS (12-FT MAX. WIDTH RECOMMENDED)

## DIMENSIONS

- A = OVERALL GATE HEIGHT \_\_\_\_\_
- B = CLEAR HEIGHT \_\_\_\_\_
- C = OVERALL GATE WIDTH \_\_\_\_\_
- D = OPENING WIDTH \_\_\_\_\_



SINGLE PANEL VERTICAL GATE ASSEMBLY

DATE: 7-24-07  
DRN BY BRT

SPVG INFO

REV 1